



3413 W. Alberta
Edinburg, Texas 78539
Phone: (956) 683-8022
FAX: (210) 568-6158
www.archemtexind.com

Product Information Bulletin CTI-553

DESCRIPTION:

CTI-553 is a color coded water soluble performance product that has been designed to unload produced fluids from gas wells, especially when the hydrocarbon content (condensate) is equal to or greater than the produced water content.

CTI-553 is a synergistic blend of several water soluble components that work together to form a with a high water content.

CTI-553 has a high tolerance for liquid hydrocarbons and has low emulsions forming tendencies.

USAGE:

CTI-553 dissolves rapidly, foams quickly, and is therefore especially effective for unloading weak wells that are loading up on ½ to 1 barrel of produced water per day. **CTI-553** is also effective on wells that accumulate less than three barrels over a fairly long period of time. Most often 2 to 6 units are all that are needed to unload the well. Your **AR Chem Tex Industries LLC Representative** will work with you on designing an effective treating program.

TYPICAL PHYSICAL PROPERTIES:

Form	Solid, Cylindrical
Color	Tan
Density @ 77°F (g/ml)	1.147
Density @ 77°F (lb/gal)	9.55
pH of 1% solution	7.67

HANDLING AND STORAGE:

CTI-553 is an industrial chemical product. All safety and handling warnings on the product container and the material safety data sheets should be observed. For detailed safety and disposal information please refer to the material safety data sheet. Store in a cool, dry location.

AVAILABILITY:

CTI-553 is available in 5 gallon containers and split top 55 gallon drums from **AR Chem Tex Industries LLC**, 3413 W. Alberta, Edinburg, TX 78539.

Please call: (956) 683-8022
FAX (210) 568-6158